



Features:

- Card reading Magnetic stripe card, ISO track II
- Type Surface mount, water proof
- Operation mode Card, card and / or keypad, keypad only
- Monitor inputs Door contact, Exit push button, case tamper
- Operation temperature 0C ~ 50C
- Humidity 20%~90% RH, Non condensation
- Power supply 12V DC
- Transmission rate 4,800 bps, N.8.1 (optional for 300 ~ 19,200 bps)
- Keypad With brief 3 X 4 membrane keypad for system programming and password entry
- Interface RS-485 or Wiegand output or TTL(optional)
- Dimensions 120(L) x 83(W) x 30(H) mm
- Weight 450g 5%
- Allow 3000 cards capacity based and expand 9,999 cards capacity for Access control function.
- Operating mode-card only, card + door code, cards / door code.
- Easy to install, low and designed for indoor or outdoor use .
- Completed duress code, variable door release, door time and alarm time, error trials.
- Non-volatile EEPROM to store system parameters.
- ARM / DISARM function
- With CPU watch-dog function to prevent malfunction.
- Windows XP software supported the LAN system.

Applications:

Offices, Computer Rooms, Bank & Building societies, Hospital, Gate lift, Airports, Universities, Factories, Block main entrances, shops, Sensitive areas, Parking Control...etc.

With imaginable & comfortable and convenient for your daily life.